

SR7302 聚烷氧基醚

产品信息

名称：保坍型减水剂大单体

产品类型：聚烷氧基醚

产品说明及特性

本品主要作为生产高性能聚羧酸减水剂的大单体，采用国际先进的烷氧基化装置、PRESS 五代技术生产，产品分子量准确、外观洁白，分子量分布较窄，二醇含量低，相较 SR7301，合成的聚羧酸减水剂不仅有较强的水泥颗粒分散保持能力，还具有较好的水泥颗粒分散能力，是一款综合减水保坍型产品；除此之外，产品在实际应用时还具有掺量低、增强效果好、粘聚、引气可调等特点，可应用在现场搅拌及远距离输送的高性能、高强度(C60 以上)的商品混凝土中。

技术指标

外观 (25°C)	白色至浅黄色片状
水分 (% m/m) ⁽¹⁾	≤0.5
pH (1%水溶液) ⁽²⁾	5.0-7.0
羟值 (mg KOH/g) ⁽³⁾	21-26
不饱和度(mmol/g) ⁽⁴⁾	≥0.37
双键保留率 (%)	≥90

- (1)水分：GB/T 6283-2008
- (2)pH：GB/T 6368-2008
- (3)羟值：GB/T 7383-2007
- (4)不饱和度：GB/T 12008.6-2010

包装与贮运

本产品采用 25kg 编织袋包装；

产品无毒，不易燃，按一般化学品贮存和运输；

贮存于干燥通风处，避免阳光直射和雨淋，贮运温度不宜高于

40°C，保质期 1 年。

联系信息

4000-456-986

www.levima.cn

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.